

MB1M~MB10M

Single Phase 0.8Amp Glass passivated Bridge Rectifiers

Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Idea for printed circuit board
- Glass passivated Junction chip
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed
250°C/10 seconds at terminals

Mechanical Data


Case: Molded plastic body

Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

Polarity: Polarity symbol marking on body

Mounting Position: Any

Weight : 0.008 ounce, 0.22 grams



Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	MB1M	MB2M	MB4M	MB6M	MB8M	MB10M	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	100	200	400	600	800	1000	VOLTS
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	VOLTS
Maximum DC blocking voltage	V_{DC}	100	200	400	600	800	1000	VOLTS
Maximum average forward rectified current at $T_L=30^\circ\text{C}$ On glass-epoxy P.C.B	I_{AV}	0.8						Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30.0						Amps
Maximum instantaneous forward voltage at 0.8A	V_F	1.0						Volts
Maximum DC reverse current $T_A=25^\circ\text{C}$ at rated DC blocking voltage $T_A=125^\circ\text{C}$	I_R	5.0 500						μA
Typical junction capacitance (Note 1)	C_J	15.0						pF
Typical thermal resistance	R_{qJA}	75.0						$^\circ\text{C/W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150						$^\circ\text{C}$

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

Ratings And Characteristic Curves

MB1M THRU MB10M

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS




FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE

